



# MOTOR CYCLE OIL

# SYN 4T

# 10W-40

## Product Description:

**MOTOR CYCLE OIL SYN 4T 10W-40** is a high performance 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air/water-cooled 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures

**MOTOR CYCLE OIL SYN 4T 10W-40** 40 is based on high quality synthetic technology Hydrocracked and hydro treated base stocks in combination with a special selected additive package to obtain the following properties following properties:

- Outstanding thermo-oxidative stability.
- Exceptional antiwear, antirust and anticorrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

**MOTOR CYCLE OIL SYN 4T 10W-40** exceeds the following performance criteria:

**API SN JASO MA/MA2**



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	858
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	14.9
Viscosity Index		ASTM D2270	
Viscosity CCS @-25°C, max	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-27
Total Base Number	mgKOH/g	ASTM D2896	8.5

**Product Nr:** 42995  
**Date Superseded:-**

**Date Issued:** 2-2-2021  
**Revision nr:** -